



HP Latex 3200 Printer

Respond fast to urgent needs with versatile
HP Latex printing up to 3.2 m (126 in)



Do diverse, high-quality applications

- Versatile HP Latex Technology and HP Latex Optimizer deliver high image quality at speeds up to 77 m² (830 ft²)/hr¹
- Superior indoor quality beats UV²—smooth transitions, sharp image quality, and preserve media texture
- Handle demanding tiling jobs with confidence —color consistency ≤ 1 dE2000 (95% of colors) in tiling mode³

Keep production in-house

- Respond to increasingly shorter turnaround times without sacrificing quality
- HP helps keep you up and running with direct support, including HP remote diagnostics⁴
- Stay in control in-plant and online—HP Print Beat application, printer status beacon, HP Latex Mobile⁵

Enable higher profitability

- You can save time and money—with automatic maintenance, no daily printhead maintenance is required
- Minimize labor costs—a single operator can manage up to four printers at the same time
- Reduce media waste—the HP Latex Media Saver preserves up to 1 linear meter each time you load a roll

For more information, please visit
hp.com/go/Latex3200

Join the community, find tools, and talk to experts.
Visit the HP Latex Knowledge Center at
hp.com/communities/LKC

¹ Printed in Indoor High Quality mode (6-pass, 6-color, 100%).

² Based on HP internal testing of prints produced using Indoor High Quality mode (6-pass, 6-color, 100%) at 77 m² (830 ft²)/hr compared to similar performance of select UV printers under \$400,000 USD as of March 2017.

³ The color variation inside a printed job, when printed with tiling optimized media, has been measured to be with maximum color difference ≤ 1 dE2000 (95% of colors) in "Optimize for tiling" mode. Tested on Ahlstrom 5087 wallpaper with stable printing condition within a stable media and a nominal printer. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. 5% of colors may experience variations above the specs mentioned. Backlit substrates measured in transmission mode may yield different results.

⁴ HP remote monitoring and diagnostics requires an upgrade to the service contract with HP.

⁵ HP Latex Mobile is compatible with Android™ 4.1.2 or later and iOS 7 or later, and requires the printer and the smart phone or tablet to be connected to the Internet.

HP Latex 3200 Printer (3.2 m / 126 in)

End-to-end sustainability—a better approach

HP Latex Technology delivers all the certifications that matter to your operators, your business, and the environment.⁶



UL ECOLOGO⁷

Using water-based inks eliminates exposure to inks with hazard warning labels and high solvent concentrations, and simplifies ventilation, storage, and transportation requirements.

HP Latex Inks enable more differentiation—odorless prints go where solvent and UV can't.



UL GREENGUARD GOLD⁸

HP is designing end-to-end sustainability into large-format printing.



HP Planet Partners Program⁹
HP Large Format Media take-back program¹⁰



HP Latex Optimizer
High image quality at high speed




HP Latex Inks
Odorless prints, with scratch resistance comparable to hard-solvent inks on SAV and PVC banner¹¹




HP OMAS & spectrophotometer
Reliable print quality—get the color and quality you expect



HP Latex printheads
1200 dpi native resolution—high image quality over the life of the printer



High-efficiency curing
Instant dry—prints are completely dry immediately after printing



Automatic maintenance
Automatic drop detection and nozzle replacement



⁶ Based on a comparison of HP Latex Ink technology to competitors with leading market share as of December, 2013 and analysis of published MSDS/SDSs and/or internal evaluation. Performance of specific attributes may vary by competitor and ink technology/formulation.

⁷ Applicable to HP Latex Inks. UL ECOLOGO® Certification to UL 2801 demonstrates that an ink meets a range of multi-attribute, lifecycle based criteria related to human health and environmental considerations (see ul.com/EL).

⁸ Applicable to HP Latex Inks. UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg or greenguard.org.

⁹ Visit hp.com/recycle to see how to participate and for HP Planet Partners program availability; program may not be available in your area. Where this program is not available, and for other consumables not included in the program, consult your local waste authorities on appropriate disposal.

¹⁰ HP Large Format Media take-back program availability varies. Some recyclable HP papers can be recycled through commonly available recycling programs. Recycling programs may not exist in your area. See HPLFMedia.com/hp/ecosolutions for details.

¹¹ Scratch-resistance comparison based on testing third-generation HP Latex Inks and representative hard-solvent inks. Estimates by HP Image Permanence Lab on a range of media.

¹² Printing double-sided backlit applications requires the optional HP Latex 3000 Double-sided Day Night Kit. Front-to-back image registration accuracy of 2 mm or better when using certified PVC banner and paper media, see hp.com/go/mediasolutionslocator.

¹³ HP Latex Mobile is compatible with Android™ 4.1.2 or later and iOS 7 or later, and requires the printer and the smart phone or tablet to be connected to the Internet.

HP Latex Technol

HP Latex 3200 Printer



Dual roll spindles

Double throughput when working with rolls up to 1.6 m (63 in)



Ink collector kit (optional)

Print unlined mesh banner and porous textiles




Double-sided day night kit (optional)¹²

Easily produce double-sided backlit applications for color-accurate outdoor advertising displays in any light—front or backlit



Proofing lights

Output and print zone LED lighting for on-the-fly visual inspection



Media saver

Preserve up to 1 linear meter each time you load a roll



Printer monitoring tools

Improve operational efficiency with the printer status beacon, HP Latex Mobile,¹³ HP PrintBeat



Internal print server

Efficiently manage the job queue and settings



Technical specifications

Printing	Printing modes	27 m ² /hr (290 ft ² /hr) - High Saturation Backlits (18-pass 6c 230%) 44 m ² /hr (470 ft ² /hr) - Textiles and Canvas (10-pass 6c 170%) 77 m ² /hr (830 ft ² /hr) - Indoor High Quality (6-pass 6c 100%) 120 m ² /hr (1290 ft ² /hr) - Outdoor (3-pass 6c 80%) 180 m ² /hr (1950 ft ² /hr) - Billboard (2-pass 4c 70%)
	Print resolution	Up to 1200 x 1200 dpi
	Ink cartridges	Black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer
	Cartridge size	5 liter
	Color consistency	Maximum color difference (95% of colors) ≤ 2 dE2000; ≤ 1 dE2000 in "Optimize for tiling" mode ¹⁴
Media	Handling	Roll-to-roll, roll-to-freefall, roll-to-collector, dual-roll, double-sided blackout, double-sided backlit (optional), ink collector (optional)
	Media types	Banners, self-adhesive vinyls, films, papers, wallcoverings, canvas; mesh and porous textiles with optional ink collector
	Roll size	Single roll up to 3.2 m (126 in) Dual roll up to 2 x 1.6 m (2 x 63 in)
	Roll weight	Single roll up to 160 kg (350 lb) Dual roll up to 2 x 70 kg (2 x 155 lb)
	Roll diameter	Up to 30 cm (11.8 in)
	Thickness	Up to 0.4 mm (0.015 in), by default Up to 2.0 mm (0.08 in), with custom carriage height setting
	Double-sided blackout	Registration accuracy 5 mm/m (0.06 in/ft), intended for double-sided PVC blackout banners
Double-sided backlit (optional)	Registration accuracy of 2 mm (0.08 in), ¹⁵ intended for double-sided backlit outdoor advertising applications	
Dimensions (w x d x h)	Printer:	598 x 172 x 187 cm (235 x 68 x 74 in)
	Shipping:	586 x 193 x 216 cm (231 x 76 x 85 in)
Weight	Printer:	1750 kg (3860 lb); Shipping: 2510 kg (5530 lb)
What's in the box	HP Latex 3200 Printer; HP 881 Latex Printheads; HP 881 Latex Cleaning Roll; 126-in spindles (x2); 126-in dual roll spindles (x2); dual roll center support; HP Internal Print Server; documentation software; user manual; media edge holders (x4); Original HP sample media; cleaning supplies; spindle supports (x2); pneumatic gun	
Environmental ranges	Standard operating conditions:	
	Temperature: 15 to 30°C (59 to 86°F)	
	Humidity: 20 to 70% RH (non-condensing)	
	Optimal IQ operating conditions:	
Temperature: 20 to 25°C (68 to 77°F)		
Humidity: 30 to 60% RH (non-condensing)		
Power consumption	10 kW (typical) - Indoor High Quality mode (6-pass)	
	11 kW (typical) - Outdoor mode (3-pass)	
Certification	Safety	IEC 60950-1+A1+A2 compliant; United States and Canada (CSA listed); EU (LVD and MD compliant, EN60950-1, EN12100-1, EN ISO13849-1, EN60204-1, and EN10101-1); Russia, Belarus and Kazakhstan (EAC); Australia, New Zealand (RCM)
	Electromagnetic	Compliant with Class A requirements, including USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), Korea (KCC)
	Environmental	WEEE, EU RoHS, China RoHS, REACH, CE marking compliant
Warranty	One-year limited hardware warranty	



Ordering information

Product	1HA06A	HP Latex 3200 Printer
Accessories	L5E74B	HP Scitex Caldera Grand RIP v11 Software
	D9Z41A	HP Scitex Onyx Thrive 211 RIP Software
	M2J33A	HP Latex In-line Slitters
	J8J14A	HP Latex 3000 Double-sided Day Night Kit
	Z3R55A	HP Latex 3000 Day Night Edge Holder Kit
	Z3R56A	HP Latex 3000 Day Night Protector Media
	CZ065A	HP Latex 3000 Ink Collector Kit
	F1V49A	HP Latex 3000 Ink Collector Foams Kit
	1ML40A	HP Latex 3000 Edge Holder Kit
	CZ059A	HP Latex 126-in Carbon Fiber Spindle
	G1K80A	HP Latex 126-in Dual Roll Spindle
	T4E58A	HP Latex Media Saver Kit
	Original HP printheads	CR327A
CR328A		HP 881 Cyan/Black Latex Printhead
CR329A		HP 881 Light Magenta/Light Cyan Latex Printhead
CR330A		HP 881 Latex Optimizer Printhead
Original HP ink cartridges and maintenance supplies		CR331A
	CR332A	HP 881 5-liter Magenta Latex Ink Cartridge
	CR333A	HP 881 5-liter Yellow Latex Ink Cartridge
	CR334A	HP 881 5-liter Black Latex Ink Cartridge
	CR335A	HP 881 5-liter Light Cyan Latex Ink Cartridge
	CR336A	HP 881 5-liter Light Magenta Latex Ink Cartridge
	CR337A	HP 881 5-liter Latex Optimizer Ink Cartridge
	CR339B	HP 881 Latex Cleaning Roll
	Original HP large format printing materials	HP printing materials are designed together with HP Latex Inks and HP Latex printers to provide optimal image quality, consistency, and reliability.
HP Permanent Gloss Adhesive Vinyl REACH ¹⁶		
HP Backlit Polyester Film ¹⁷		
HP PVC-free Durable Smooth Wall Paper REACH, ¹⁶ FSC [®] certified, ¹⁸ UL GREENGUARD GOLD Certified ¹⁹		
HP Premium Poster Paper ¹⁷ FSC [®] certified ¹⁸		
For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com .		
Service kits	1UH14A	HP Latex 3000 Standard Uptime Kit
	2CA94A	HP Latex 3000 Expert Uptime Kit
	1VT19A	HP Latex 3000 Maintenance Kit
	1HA07-67012	HP Latex 3000 Service Maintenance Kit
	1HA07-67013	HP Latex 3000 Textile Service Maintenance Kit
	CZ056-67390	HP Latex 3000 Cleaning Kit
Service contracts	HP Full Hardware Support Contract with Preventive Maintenance and Proactive Monitoring	
	HP Full Hardware Support Contract	
	HP Shared Maintenance Hardware Support Contract	

¹⁴ The color variation inside a printed job, when printed with tiling optimized media, has been measured to be with maximum color difference ≤ 1 dE2000 (95% of colors) in "Optimize for tiling" mode when tested on Ahlstrom 5087 wallpaper with stable printing condition within a stable media and a nominal printer. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. 5% of colors may experience variations above the specs mentioned. Backlit substrates measured in transmission mode may yield different results.

¹⁵ Printing double-sided backlit applications requires the optional HP Latex 3000 Double-sided Day Night Kit. Front-to-back image registration accuracy of 2 mm or better when using certified PVC banner and paper media, see hp.com/go/mediasolutionslocator.

¹⁶ This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP Printing Products and Consumable Supplies.

¹⁷ HP Large Format Media take-back program availability varies. Some recyclable HP papers can be recycled through commonly available recycling programs. Recycling programs may not exist in your area. See HPLFMedia.com/hp/ecosolutions for details.

¹⁸ BMG trademark license code FSC[®]-C115319, see fsc.org. HP trademark license code FSC[®]-C017543, see fsc.org. Not all FSC[®]-certified products are available in all regions.

¹⁹ UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg or greenguard.org.

